

FLOOR STANDING SPLIT TYPE AIR-CONDITIONER

Enter a fresher world with Fujiaire's practical floor standing split type air-conditioner.



Your World Made Cooler

 **FUJIAIRE**
AIR - C O N D I T I O N E R S




2.0 hp to 3.0 hp

5.0 hp

To provide full fresh coolness and circulation to every corner.

SPECIFICATIONS

- All specifications are subject to change by the manufacturer without prior notice.
- Performance of the unit varies according to the type of compressor used.
- Nominal cooling and heating capacities are based on the following conditions:
Cooling: 27°C DB / 19°C WB Indoors
35°C DB / 24°C WB Outdoors



Cool

Crisp

Clean



Model		Indoor Unit	FFA20C1C	FFA25C1C
		Outdoor Unit	FLA20C1A	FLA25C1A
Cooling Capacity		Btu/hr	20,000	25,000
		kW	5.86	7.33
Power Source		V / Φ / Hz	220-240 / 1 / 50	
Cooling	Rated Power Input	W	1,960	2,511
	Rated Current	A	9.1	12.2
Air Flow	Indoor (Hi)	CFM / CMH	500 / 850	560 / 950
Energy Efficiency Ratio	EER	Btu/W.hr	10.20	9.96
Control System	Refrigerant / Flow Control	Type	R22 / Outdoor Capillary Tube	
	Operating Control	Type	Wireless Remote Controller & Panel	
Air Filter System		Type	Washable Saran Net	
Temperature Control		Type	Microprocessor I/C Thermostat	
Timer		Type	24 Hours	
Compressor		Type	Rotary	
Refrigerant Pipe Size	Gas	mm (Inch)	12.7 (1/2")	15.88 (5/8")
	Liquid	mm (Inch)	6.35 (1/4")	9.52 (3/8")
Noise Level	Indoor (Hi)	dB(A)	44	45
	Outdoor	dB(A)	55	56
Net Unit Dimension (WxHxD)	Indoor	mm	480 x 1730 x 280	480 x 1730 x 300
	Outdoor	mm	850 x 606 x 306	872 x 700 x 319
Packing Dimension (WxHxD)	Indoor	mm	575 x 1865 x 385	575 x 1865 x 385
	Outdoor	mm	995 x 690 x 415	990 x 780 x 410
Net Weight	Indoor	kg	33	38
	Outdoor	kg	40	53
Gross Weight	Indoor	kg	44	49
	Outdoor	kg	45	60

Model		Indoor Unit	FFA30C1C	FFA50C1C
		Outdoor Unit	FC-3016	FLA50C1A
Cooling Capacity		Btu/hr	30,000	50,000
		kW	8.79	14.65
Power Source		V / Φ / Hz	220-240 / 1 / 50	380-415 / 3 / 50
Cooling	Rated Power Input	W	3,200	4,720
	Rated Current	A	14.8	8.1
Air Flow	Indoor (Hi)	CFM / CMH	650 / 1100	1200 / 2040
Energy Efficiency Ratio	EER	Btu/W.hr	9.38	10.59
Control System	Refrigerant / Flow Control	Type	R22 / Outdoor Capillary Tube	R22 / Accurator
	Operating Control	Type	Wireless Remote Controller & Panel	
Air Filter System		Type	Washable Saran Net	
Temperature Control		Type	Microprocessor I/C Thermostat	
Timer		Type	24 Hours	Real Timer
Compressor		Type	Rotary	Scroll
Refrigerant Pipe Size	Gas	mm (Inch)	15.88 (5/8")	19.05 (3/4")
	Liquid	mm (Inch)	9.52 (3/8")	
Noise Level	Indoor (Hi)	dB(A)	49	52
	Outdoor	dB(A)	58	60
Net Unit Dimension (WxHxD)	Indoor	mm	480 x 1730 x 300	600 x 1900 x 360
	Outdoor	mm	900 x 841 x 336	1000 x 995 x 347
Packing Dimension (WxHxD)	Indoor	mm	575 x 1865 x 385	695 x 2050 x 485
	Outdoor	mm	1030 x 960 x 440	1150 x 1120 x 475
Net Weight	Indoor	kg	38	61
	Outdoor	kg	79	94
Gross Weight	Indoor	kg	49	75
	Outdoor	kg	82	102